



品番	PD	OD	BUSHING		TYPE	L	P	R	F	質量 (KG)
	データ ム径	外 径	品 番 No.	最大軸 径	形状 図番	ボス 長さ	出	引込 み	リム 幅	
SPZ 100-4	100	104	1610	42	6	25	—	27	52	1.37
SPZ 106-4	106	110	1610	42	6	25	—	27	52	1.54
SPZ 112-4	112	116	2012	50	6	32	—	20	52	1.64
SPZ 118-4	118	122	2012	50	6	32	—	20	52	1.91
SPZ 125-4	125	129	2012	50	6	32	—	20	52	2.23
SPZ 132-4	132	136	2012	50	6	32	—	20	52	2.62
SPZ 140-4	140	144	2012	50	6	32	—	20	52	3.07
SPZ 150-4	150	154	2517	60	6	45	—	7	52	3.78
SPZ 160-4	160	164	2517	60	6	45	—	7	52	4.57
SPZ 170-4	170	174	2517	60	6	45	—	7	52	5.42
SPZ 180-4	180	184	2517	60	6	45	—	7	52	6.28
SPZ 190-4	190	194	2517	60	6	45	—	7	52	7.83
SPZ 200-4	200	204	2517	60	9	45	—	3.5	52	5.25
SPZ 212-4	212	216	2517	60	9	45	—	3.5	52	6.31
SPZ 224-4	224	228	2517	60	9	45	—	3.5	52	6.90
SPZ 236-4	236	240	2517	60	9	45	—	3.5	52	7.30
SPZ 250-4	250	254	2517	60	9	45	—	3.5	52	7.69
SPZ 265-4	265	269	2517	60	12	45	—	3.5	52	8.02
SPZ 280-4	280	284	2517	60	12	45	—	3.5	52	7.81
SPZ 300-4	300	304	2517	60	9	45	—	3.5	52	10.00
SPZ 315-4	315	319	2517	60	12	45	—	3.5	52	8.71
SPZ 355-4	355	359	2517	60	12	45	—	3.5	52	11.80

品番	PD	OD	BUSHING		TYPE	L	P	R	F	質量 (KG)
	データ ム径	外 径	品 番 No.	最大軸 径	形状 図番	ボス 長さ	出	引込 み	リム 幅	
SPA 75 -1	75	80.5	1108	28	4	22	2	—	20	0.42
SPA 80 -1	80	85.5	1210	32	4	25	5	—	20	0.49
SPA 83 -1	83	88.5	1210	32	4	25	5	—	20	0.55
SPA 85 -1	85	90.5	1210	32	4	25	5	—	20	0.58
SPA 88 -1	88	93.5	1210	32	4	25	5	—	20	0.60
SPA 90 -1	90	95.5	1210	32	4	25	5	—	20	0.67
SPA 93 -1	93	98.5	1210	32	4	25	5	—	20	0.75
SPA 95 -1	95	100.5	1210	32	4	25	5	—	20	0.76
SPA 98 -1	98	103.5	1210	32	4	25	5	—	20	0.77
SPA 100 -1	100	105.5	1610	42	4	25	5	—	20	0.78
SPA 103 -1	103	108.5	1610	42	4	25	5	—	20	0.88
SPA 106 -1	106	111.5	1610	42	4	25	5	—	20	0.92
SPA 109 -1	109	114.5	1610	42	4	25	5	—	20	1.00
SPA 112 -1	112	117.5	1610	42	4	25	5	—	20	1.06
SPA 118 -1	118	123.5	1610	42	4	25	5	—	20	1.23
SPA 125 -1	125	130.5	1610	42	4	25	5	—	20	1.40
SPA 132 -1	132	137.5	1610	42	4	25	5	—	20	1.58
SPA 140 -1	140	145.5	1610	42	4	25	5	—	20	1.83
SPA 150 -1	150	155.5	1610	42	8	25	5	—	20	1.83
SPA 160 -1	160	165.5	1610	42	8	25	5	—	20	2.07
SPA 170 -1	170	175.5	1610	42	8	25	5	—	20	2.13
SPA 180 -1	180	185.5	1610	42	8	25	5	—	20	2.14