



品番	PD	OD	BUSHING		TYPE	L	P	R	F	質量 (KG)
	データ ム径	外 径	品 番 No.	最大軸 径	形状 図番	ボス 長さ	出	引込 み	リム 幅	
SPA 75 -2	75	80.5	1108	28	5	22	—	13	35	0.62
SPA 80 -2	80	85.5	1210	32	5	25	—	10	35	0.62
SPA 83 -2	83	88.5	1210	32	5	25	—	10	35	0.71
SPA 85 -2	85	90.5	1210	32	5	25	—	10	35	0.73
SPA 88 -2	88	93.5	1210	32	5	25	—	10	35	0.80
SPA 90 -2	90	95.5	1610	42	5	25	—	10	35	0.72
SPA 93 -2	93	98.5	1610	42	5	25	—	10	35	0.83
SPA 95 -2	95	100.5	1610	42	5	25	—	10	35	0.88
SPA 98 -2	98	103.5	1610	42	5	25	—	10	35	1.00
SPA 100 -2	100	105.5	1610	42	6	25	—	10	35	1.04
SPA 103 -2	103	108.5	1610	42	6	25	—	10	35	1.20
SPA 106 -2	106	111.5	1610	42	6	25	—	10	35	1.22
SPA 109 -2	109	114.5	1610	42	6	25	—	10	35	1.30
SPA 112 -2	112	117.5	1610	42	6	25	—	10	35	1.38
SPA 118 -2	118	123.5	1610	42	6	25	—	10	35	1.59
SPA 125 -2	125	130.5	1610	42	6	25	—	10	35	1.87
SPA 132 -2	132	137.5	2012	50	6	32	—	3	35	2.20
SPA 140 -2	140	145.5	2012	50	5	32	—	3	35	2.50
SPA 150 -2	150	155.5	2012	50	5	32	—	3	35	3.05
SPA 160 -2	160	165.5	2012	50	5	32	—	3	35	3.60
SPA 170 -2	170	175.5	2012	50	15	32	—	3	35	3.28
SPA 180 -2	180	185.5	2012	50	9	32	—	1.5	35	3.41
SPA 190 -2	190	195.5	2012	50	9	32	—	1.5	35	3.72
SPA 200 -2	200	205.5	2517	60	8	45	10	—	35	4.74
SPA 212 -2	212	217.5	2517	60	8	45	10	—	35	5.31
SPA 224 -2	224	229.5	2517	60	13	45	10	—	35	6.02
SPA 236 -2	236	241.5	2517	60	13	45	10	—	35	6.20
SPA 250 -2	250	255.5	2517	60	13	45	10	—	35	6.30
SPA 280 -2	280	285.5	2517	60	13	45	10	—	35	6.43
SPA 300 -2	300	305.5	2517	60	13	45	10	—	35	7.30

品番	PD	OD	BUSHING		TYPE	L	P	R	F	質量 (KG)
	データ ム径	外 径	品 番 No.	最大軸 径	形状 図番	ボス 長さ	出	引込 み	リム 幅	
SPA 75 -3	75	80.5	1108	28	5	22	—	28	50	0.82
SPA 80 -3	80	85.5	1210	32	5	25	—	25	50	0.83
SPA 85 -3	85	90.5	1210	32	5	25	—	25	50	0.99
SPA 88 -3	88	93.5	1210	32	5	25	—	25	50	1.10
SPA 90 -3	90	95.5	1610	42	5	25	—	25	50	1.03
SPA 93 -3	93	98.5	1610	42	5	25	—	25	50	1.10
SPA 95 -3	95	100.5	1610	42	5	25	—	25	50	1.19
SPA 98 -3	98	103.5	1610	42	5	25	—	25	50	1.25
SPA 100 -3	100	105.5	1610	42	6	25	—	25	50	1.30
SPA 103 -3	103	108.5	1610	42	6	25	—	25	50	1.40
SPA 106 -3	106	111.5	1610	42	6	25	—	25	50	1.54
SPA 109 -3	109	114.5	1610	42	6	25	—	25	50	1.70
SPA 112 -3	112	117.5	2012	50	5	32	—	18	50	1.58
SPA 118 -3	118	123.5	2012	50	6	32	—	18	50	1.84
SPA 125 -3	125	130.5	2012	50	6	32	—	18	50	2.25
SPA 132 -3	132	137.5	2012	50	6	32	—	18	50	2.58
SPA 140 -3	140	145.5	2517	60	6	45	—	5	50	2.90
SPA 150 -3	150	155.5	2517	60	6	45	—	5	50	3.64
SPA 160 -3	160	165.5	2517	60	6	45	—	5	50	4.37
SPA 170 -3	170	175.5	2517	60	6	45	—	5	50	5.28
SPA 180 -3	180	185.5	2517	60	6	45	—	5	50	6.12
SPA 190 -3	190	195.5	2517	60	6	45	—	5	50	7.06
SPA 200 -3	200	205.5	2517	60	9	45	—	2.5	50	5.72
SPA 212 -3	212	217.5	2517	60	9	45	—	2.5	50	6.30
SPA 224 -3	224	229.5	2517	60	12	45	—	2.5	50	6.20
SPA 236 -3	236	241.5	2517	60	12	45	—	2.5	50	6.87
SPA 250 -3	250	255.5	2517	60	12	45	—	2.5	50	7.30
SPA 280 -3	280	285.5	2517	60	12	45	—	2.5	50	8.43
SPA 300 -3	300	305.5	3020	75	13	51	1	—	50	9.90